# **Clinic Access Key Assist** How to take required measurements

It is important to take measurements for inclusion in your Access Key Assist. Potential customers will need these measurements to make an informed choice on the suitability of your venue.

This guide provides instructions for taking measurements and provides examples.

#### **Measuring Tape**

- Measuring tapes are available in a variety of sizes.
- A three metre or five-metre-long tape will be sufficient.
- Please check the tape used has a metric scale on its ribbon. Many tapes will have both an imperial scale (inches
- and feet) on one side of the ribbon and a metric scale (millimetres and centimetres) on the other.
  - Please record your measurements in mm.

1	-		
	-	•	

## Horizontal width of main entry door

Measure the clear width of the main entry door as shown. Please ensure to measure the clear space through the door opening.

- 1. Open door to its widest width.
- 2. Using measuring tape, measure from edge of actual door to opposite frame.
- 3. Record measurement in mm.

## Horizontal width of accessible toilet door

Measure the clear width of the accessible toilet door as shown on the right. Please ensure to measure the clear space through the door opening.

- 1. Open door to its widest width.
- 2. Using measuring tape, measure from edge of actual door to opposite frame.
- 3. Record measurement in mm.



#### **Reception desk**

Measure the height of the main service counter and the lower height counter, if applicable as shown on the left.

- 1. Please measure from the ground to the actual serving height.
- 2. Record measurements in mm.

## **Drinking Fountain**

Measure the operating height of the drinking fountain and the knee clearance if applicable, as shown on the right. The knee clearance is the actual space for the knees of a person using a wheelchair to go when they roll up to the fountain.

- 1. Measure from the ground to the operating button.
- 2. If applicable, please measure the knee clearance of water fountain station from beneath top of fountain to ground.
- 3. Record measurements in mm.



## Standard consultancy room door

Measure the clear width of a standard consultancy room door as shown on the left. Please ensure to measure the clear space through the door opening.

- 1. Open door to its widest width.
- 2. Using measuring tape, measure from edge of actual door to opposite frame.
- 3. Record measurement in mm.







knee clearance

operating height